

RAD HIGH SPEED


Extreme duty torque wrenches with high RPM productivity

RAD High Speed torque wrenches incorporate a precision-engineered high-speed gearbox designed for faster run down and quick reaction point positioning on time sensitive bolting applications.

- The two-speed models feature a unique full automatic gearbox design, eliminating the time consuming switch between high and low speed gear.

FRL Unit:

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm)		RPM	WEIGHT (Kg)	NOISE LEVEL	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
			LOW	HIGH							
19774	14GX-2	0.75"	475	1400	85	4.5	80 db	261	63	70	205
19775	20DX-2	1.0"	700	2000	50	4.7	80 db	251	68	70	205
19776	34GX-2	1.0"	950	3400	44	7.5	80 db	305	78	84	254
24952	40DX-2	1.0"	1400	4000	49	7.3	80 db	309	81	83	254

Accuracy of +/-4%, Repeatability of +/-2%

RAD TORQUE SYSTEMS